



## High-Accuracy GNSS Receiver for Your Smartphone, Tablet, or Notebook Computer

*The Arrow 100® is designed specifically to use with a variety of mobile devices, including your smartphone, tablet, or notebook computer. It incorporates rock-solid, wireless Bluetooth® technology that works with Android, iOS, and Windows® devices, making it obsolete-proof. Contemplating switching from an iPhone to an Android phone or vice-versa? No problem, the Arrow 100 works smoothly with both.*

### Use the Mobile GIS Software of Your Choice

Seems like a new mobile GIS software is being offered each week? With the Arrow 100 you will not be tied to legacy GNSS receiver hardware or GIS software, it will grow with you. The Arrow 100 feeds submeter accuracy to every app on your Android or iOS device, even Google or Apple maps! Esri Collector, Survey123 and QuickCapture, Futura, AmigoCloud, Mapit, GeoJot, iCMTGIS, it works seamlessly with all of them and many more mapping apps.

### Real-time, Worldwide Accuracy

The Arrow 100 takes advantage of GPS, GLONASS, Galileo, BeiDou, and free SBAS corrections in most regions of the world. For SBAS, North America is covered by WAAS, Europe and North Africa by EGNOS, India is covered by GAGAN, Japan by MSAS, and Australasia by their own system. With the above-mentioned free SBAS the Arrow 100 provides 30 to 60 cm real-time accuracy.

For more details,  
[www.eos-gnss.com](http://www.eos-gnss.com)

# ARROW 100®

ARROW Series®  
for Submeter GNSS Positioning

### Key Features:

- Full GNSS (GPS, GLONASS, Galileo, BeiDou)
- 100 % Android, iOS, Windows compatible
- 30 to 60 cm real-time accuracy using free SBAS
- Supports all mobile GIS software



### Works Where Other Receivers Can't

The Arrow 100 was designed specifically with GIS users in mind. It squeezes more accuracy from SBAS corrections than any other receiver in the world. With its patented technology, you can use it under trees, around buildings, and in rugged terrain where other receivers will fail to deliver. Where having GPS is just not enough, the Arrow 100 uses GLONASS, Galileo, and BeiDou signals from at least 100 satellites. Real-time results in the field optimize your efficiency with no post-processing required!



# Specifications

## GPS Sensor

Receiver Type:	L1/G1/E1/B1, GPS, GLONASS, Galileo, BeiDou with carrier smoothing
Channels:	158-channel, parallel tracking
Number of Tracked Satellites:	12 GPS (15 when no SBAS) 12 GLONASS 15 Galileo 22 BeiDou
SBAS Support:	3-channel, parallel tracking WAAS, EGNOS, MSAS, GAGAN (SBAS ranging where supported)
Update Rate:	1 Hz Default, optional 10 Hz and 20 Hz
DGNSS Horizontal Accuracy:	< 30 cm HRMS
SBAS Accuracy:	< 60 cm 2dRMS, 95% confidence <sup>1</sup> (< 30 cm HRMS, < 25 cm CEP)
Horizontal Accuracy:	< 2.5 m 2dRMS, 95% confidence <sup>1</sup> (autonomous, no SA) < 20 cm 2dRMS, 95% confidence <sup>1</sup>
Optional Proprietary RTCM:	1 cm + 1 ppm <sup>1</sup>
Optional Single Frequency RTK:	< 60 sec typical (no almanac or time)
Cold Start:	< 1 sec
Reacquisition:	< 1 sec
Maximum Speed:	1,850 kph / 1,150 mph / 999 knots
Maximum Altitude:	18,288 m (60 000 ft)

## Communication

Port:	Bluetooth, USB 2.0, serial (optional)
Bluetooth Transmission:	Class 1, 300 m typical range <sup>2</sup> , up to 1 km
Bluetooth Frequency:	2.400 - 2.485 GHz
Fully Bluetooth Pre-Qualified:	Bluetooth 2.1 + EDR
Supported Bluetooth Profiles:	SPP and iAP
Data I/O Protocol:	NMEA-0183, RTCM SC-104, Binary
Raw Measurement Data:	Binary and RINEX
Correction I/O Protocol:	RTCM, Optional Proprietary format
GNSS Status LED:	Power, GNSS, DGNSS, DIFF, Bluetooth
Battery Status LED:	5 LED Indicator

## Power

Battery Type:	Field replaceable, rechargeable Lithium-Ion pack (rechargeable inside unit or separately)
Battery Capacity:	Battery Operating Time: 12+ hours <sup>3</sup>
Charging Time:	4 hours (vehicle charger available)
Antenna Voltage Output:	5 VDC
Antenna Input Impedance:	50 Ohms

## Environmental

Operating Temperature:	-40°C to +85°C (-40°F to +185°F) <sup>3</sup>
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Compliance:	FCC, CE, RoHS and Lead-free



Eos Positioning Systems Inc.  
Terrebonne (Quebec), Canada  
Tel: (450) 824-3325  
[www.eos-gnss.com](http://www.eos-gnss.com) | [info@eos-gnss.com](mailto:info@eos-gnss.com)

## Mechanical

Enclosure Material:	Xenoy
Enclosure Rating:	Waterproof, IP-67
Immersion:	30 cm, 30 minutes
Dimensions:	12.5 x 8.4 x 4.2 cm (4.92 x 3.3 x 1.65 in.)
Weight:	372 g (0.82 lbs)
Data Connectors:	Mini USB Type B Receptacle
Antenna Connector:	SMA Female

## Antenna

Frequency Range:	L1, G1, E1, B1
Gain (without cable):	26 dB (+/- 2 dB), 35 mA
Voltage:	+4.5 to +15 VDC
Impedance:	50 Ohms
Dimensions:	6.6 diam. x 2.7 cm (2.61 x 1.05 in.)
Weight (without cable):	114 g (0.25 lbs) with removable magnet mount)
Antenna Connector:	SMA Female
Finish:	Fluid Resistant
Temperature:	-55°C to +70°C (-67°F to +158°F)
Immersion:	30 cm, 30 minutes

## Standard Accessories

Li-Ion Battery Pack (Field replaceable)  
12VDC Power Supply  
Belt/Shoulder Carrying Case  
Precision Antenna with 1.5 m cable  
Soft Hat for Antenna  
USB Cable


## Field Activated Options

10 Hz, 20 Hz Output Rate  
Base Station RTCM Output  
Single Frequency RTK for 1-3 cm

### NOTES:

1. Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services) and ionospheric activities.
2. Transmission in free space
3. Lithium-Ion battery performance degrades below -20°C (-4°F)

© Copyright May 2020, Eos Positioning Systems Inc. All rights reserved. Specifications subject to change without notice. Arrow 100®, Arrow Series® are registered trademarks of Eos Positioning Systems Inc., Canada. The Bluetooth™ trademarks are owned by Bluetooth SIG, Inc, U.S.A. All other trademarks are the property of their respective owners.

Made in Canada 



### Forest it Design

Forest it Design is a leading provider of rugged mobile computers, all-in-One PC:s, measurement instruments and GPS/GNSS solutions. The company has offices in Sweden, UK, Germany and Finland.

**Sweden**  
+46 (0) 370 69 08 10  
[mail@forest-it.se](mailto:mail@forest-it.se)

**UK**  
+44 (0) 127 328 6561  
[mail@forest-it.com](mailto:mail@forest-it.com)

**Germany**  
+49 (0) 6081 5769980  
[mail@forest-it.de](mailto:mail@forest-it.de)

**Finland**  
+358 (0) 40 197 0259  
[mail@forest-it.fi](mailto:mail@forest-it.fi)

Med reservation för feltryck och ändringar. Forest it Design 2021-03-03.